



### Applications

- Self-drilling, double anchorage fixing for plasterboard: thickness 10 to 13 mm with or without insulation (polystyrene, etc...)
- Bathroom accessories
- Kitchen cabinets
- Radiators, electrical enclosures

### Material

- Anchor body-zamak 3, NFA 55.010
- Special screw supplied, head type PZ2

## Special fixing for plasterboard: double anchorage

### Technical data

TYPE	Max thick of part to be fixed (mm)	Ø thread (mm)	Ø anchor head (mm)	Ø screw head (mm)	Screw length (mm)	Total anchor length (mm)	Eurocode
	$t_{fix}$	$d$	-	$D$	$L1$	$L$	
TP 12	12	4,5	16	9,2	45	39	061190
TF 30	30	4,5	16	8,8	60	39	061200

TP = Pan head TF = Countersunk head

### Recommended and ultimate loads (kN)



TYPE	Plasterboard BA 10		Plasterboard BA 13	
	$N_{rec}$	$N_{u,m}$	$N_{rec}$	$N_{u,m}$
TP12				
TF30	0,084	0,42	0,12	0,60

TYPE	Plasterboard BA 10		Plasterboard BA 13	
	$V_{rec}$	$V_{u,m}$	$V_{rec}$	$V_{u,m}$
TP12				
TF30	0,23	1,15	0,28	1,40